![McIntire Business Products logo]

ALM3230 Automatic Laminator

Labor free automation with feeding, laminating, and trimming at the touch of a button!

- Heated rollers for crystal clear scratch-free laminations
- Adjustable trim for full encapsulation or precise flush cut
- Sits on a tabletop or optional stand
- Green Button Operation: touch the button and walk away for labor-free, fully trimmed and laminated sheets
- ASAP adhesive laminating films in 1.5, 3, and 5 mil, gloss, matte, and Elegant Silk Matte adheres to hard-to-laminate digitally printed sheets

Eliminate time-consuming, costly hand feeding and trimming in laminating with the new value priced ALM3230 lamination system!

ALM Exclusive ASAP Roll Film

Perfect for Digital Print technology
Anti-static properties

Gloss, Matte, and Elegant Silk Matte

1.5mil, 12.6" x 984 ft
3.0mil, 12.6" x 492 ft
5.0mil, 12.6" x 328 ft
1.2mil, 12.6" x 984 ft, One Side Nylon set (Gloss & Matte Versions)

ALM 3230 Specifications

Small Foot Print – less than 4 sq. ft.
Table Top or optional stand with locking roller casters
115 Volt, 15 amp service with economy mode
Ultra quick warm up of less than 5 minutes
Virtually Unattended Operation
Digital Sheets sizes: 13"x19", 12"x18", 11"x17", 8.5"x11"
Laminates copy paper up to 100lb cover stock
Automatic two side lamination or short one side work
Adjustable Automatic Flush or Sealed edge trim
1 year parts and labor warranty

Model ALM3230

Laminating Speed Fixed speed at 40"/min.
Temperature Range 170-270°F
Ultra Fast Warm-Up Time Approximately 5 minutes
Film Thickness 1.5, 3, and 5 mil
Thickness of Objects 20lb bond - 100lb cover
Paper Feeding Capacity 100 Sheets, Adjustable Paper Guide
Applicable Sizes:
    Letter Paper Size 8½" x 11"
    Tabloid Paper Size 11" x 17"
    Digital Paper Size 12" x 18"
    Digital Paper Size 13" x 19"
Trimming Methods (2 modes) Flush trim or edge seal for all 4 sides of the print
Operation Panel LCD display for start, stop, temperature, and trim settings, leading and trailing edge side cuts are adjustable
Other Features Laminated sheet counter, Film tension control, Roller gap lever, Paper thickness feeder adjustment lever
Power Consumption 900W
Power Supply AC 120V (60Hz)
Net Weight Laminator 100 Lbs. Stand: 48.5 Lbs.
Optional Accessories Rolling Stand