

**Commercial Grade 6 or 10 Roller Laminators
with Programmable Memory Settings**

**Laminates
Up To 14 Mil!**



Ultra-X10 (Fastest Speed)




Ultra-X6



Ultra-XL (Extra Large 18.9" Opening)



Programmable Memory Settings
Allows you to save the ideal temperature and speed for your most frequent projects.



Blazing Fast Speed
The 10 roller heat system (X10 only) grants you one of the fastest laminating speeds in its class (i.e. 142" per minute).



Auto Shutoff
Automatically cools and shuts down the machine after usage, to prolong the life of your laminator.



Extra Large Opening
The 18.9" opening (XL only) allows you to laminate with extra large pouches (i.e. 18" x 24").

AKILES ProLam Ultra-X Series

The Akiles ProLam Ultra-X Series laminators possess superior quality and functionality combined with commercial grade design. Its multiple roller heat system produces professional, crystal-clear and bubble-free pouches every time.

10 Roller Heat System

6 heated rollers + 2 cold rollers + 2 ejector rollers guarantees professional grade results at blazing fast speeds (X10 only).

Removable Cover

Allows quick access to the rollers with easy to remove thumb screws.

LCD Control Panel

Backlit LCD display with labeled keypad makes it easy to operate.



Settings Guide

Shows the recommended temperature and speed settings for different pouch thicknesses.

13" and 18.9" Capacities

The large 13" (X6 / X10) or extra large 18.9" (XL) throat allows the machine to laminate a wide array of pouch sizes.

Air Cooling System

Patented internal cooling system ensures the laminator stays cool to the touch while in use.

Programmable Memory Settings

Memorize the ideal temperature & speed settings for your most frequently used pouches.

ProLam Ultra	X6	XL	X10
Throat Capacity	13" (330 mm)	18.9" (480 mm)	13" (330 mm)
Max Laminating Speed	59" / min	47" / min	142" / min
Max Pouch Thickness	14 mil (350 mic)		
Max Laminating Thickness	1/8" (3 mm)		
Heated Rollers System	4 Hot / 2 Cold		6 Hot / 4 Cold
Memory Settings	2 Programmable (Temperature & Speed)		
Speed Control	9 Settings		
Operating Temperature	32°F - 284°F		32°F - 320°F
Dimensions	21" x 10.5" x 5"	27.25" x 10.5" x 5"	14" x 25.75" x 5.75"
Weight	35 lbs (16 Kg)	44 lbs (20 Kg)	57 lbs (26 Kg)
Power Consumption	1050 W	1200 W	1560 W
Warranty	1 Year		