


## ➔ 352F PROFESSIONAL SERIES TABLETOP FOLDER

dual roller friction feed system accepts a wide variety of stocks, including carbonless sheets | adjusts in seconds for standard and custom folds | variable speed control | powered exit conveyor | sheet separation from top of fanned stack | polyurethane foam rollers eliminate the need for fold roller pressure settings | heavy-duty, non-flexing side frames | needle bearings for high speed production | optional extended delivery system, crossfold for right-angle folding, and slitting, scoring, and perforating attachments

Dimensions (D x W x H): 22 1/4 x 41 3/4 x 14 1/2 inches, Shipping weight: 105 lbs.




### DUAL FEED ROLLERS



The dual roller feed system folds a wide range of stock.

### POWERED CONVEYOR



A powered exit conveyor ensures smooth ejection of folded paper.

### ➔ 352F

Speed	22,000 sheets/hr*
Paper size	2" x 2 3/4" to 14" x 21 1/4"
Paper weight	13 to 110 lbs.*
Sheet capacity	300*
Power supply	115 V, 60 Hz

\* may vary due to variations in paper and power supply



128K Hall Street • Concord, NH 03301  
(603) 225-3400 • FAX (603) 225-4014  
**800-847-2463 • www.mbp-inc.com**