

## Phoenix 2700-DHP Dual Heat Laminator - Production Model

The Phoenix 27" Production Model is a smart choice for production environments looking for an economical, easy to use unit. The tabletop design is great for smaller working areas.

Designed to offer maximum flexibility, the unit allows the use of either 1" or 2-1/4" core laminating films in thicknesses of 1.5 mil to 10.0 mil. The unit can also be gapped incrementally at settings of 1/16", 1/8", 3/16" and 1/4" to accomplish mounting on a large variety of substrates.



With safety and energy savings concerns in mind, the Phoenix 2700 includes the latest innovations. Safety measures include safety latches on the feed tray and a safety shield preventing the unit from running if they are not in place. To conserve energy, the machine will drop into a sleep mode (175°) if unit has been idle for 1/2 hour. If there is no activity on the unit for 3 hours, the heaters turn off.

### FEATURES:

- Laminates up to 27" wide
- Accepts 1.5 to 10.0 mil
- Cooling fans for heavier films
- Clear polycarbonate safety shield
- Reverse feature
- 2-1/4" diameter heated rollers
- Feed tray with paper guide
- Adjustable supply roll tension
- Roller can gap from 1/16" to 1/4" for mounting
- Auto shut-off with 175° hold temperature
- Chain and sprocket drive
- Heavy-duty 24V DC motor
- Easy alignment of top and bottom rolls with standard widths marked on supply shaft

### SPECIFICATIONS:

- Film width capacity 27"
- Speed 0 - 10 feet per minute
- Warm-up time 20 minutes
- Film supply core size 1" & 2-1/4"
- Machine dimensions 36.5"W x 16"H x 18"D
- 1 year warranty from manufacturer
- Shipping dimensions 43"W x 22"H x 21"D
- Net weight 120 lbs.
- Shipping weight 135 lbs.
- Heater wattage 1600 watts
- Power requirements 13.3 amps, 120VAC, 60Hz