

→ 4705 MANUAL CUTTER

"SCS" (Safety Cutting System) features: hinged, transparent safety guard on front table (locks automatically while cutting); transparent safety cover on rear table; safety catch (locks blade lever in up position); blade change from front without removing machine covers; blade changing device covers cutting edge of blade; blade depth adjustment from outside of machine; cutting stick can be turned or changed from outside of machine | Solingen steel blade | solid steel blade carrier and adjustable blade guides | extra large cut lever requires minimal effort | spindle clamping system applies even pressure along entire cutting width | spindle-guided back gauge with calibrated crank | precision back gauge measuring scale on front table | all-metal construction | optional stand (shown)

Dimensions (D x W x H): 34 1/2 x 20 inches (50 H with stand), Shipping weight: 297 lbs. (320 with stand).



LOCKING SAFETY GUARD



The hinged front safety guard locks in the lowered position during cutting process.

SPINDLE CLAMP



A solid spindle clamp applies variable, even pressure along the entire cutting width.

EASY CUTTING STICK CHANGE



Cutting sticks can be turned or changed from outside of machine.

TRIUMPH 4705

Cutting width	18 ¾"
Cutting height	2 3/4"
Narrow cut	1 3/16"
Cutting length behind blade	18 ¼"
Table length in front of blade	8 1/8"

