

## VRCut<sup>®</sup> Ready **TRIUMPH** 7260

28" programmable cutter with hydraulic clamp, power back gauge, touchpad control module, and IR safety light beams on front table.



Register on  
Lyrod.com to  
receive your free  
VRCut Hardware  
Kit

- A IR SAFETY CURTAIN**  
IR light beam safety curtain covers work area to ensure the highest level of operator safety.
- B ELECTRONIC HAND WHEEL**  
The electronic hand wheel, with infinitely variable speed control, is used for manual back gauge positioning.

- C EASY CUT BLADE ACTIVATION BARS**  
Patented EASY CUT blade activation bars ensure true, two-hand operation and allow blade and clamp to be activated independently.
- D SAFE BLADE CHANGES**  
Blade changes can be made without removing machine covers. Handy blade changing device covers the cutting edge of blade.
- E HARDWARE KIT**  
Register on Lyrod.com to receive your free VRCut Hardware Kit. Everything you need, right out of the box.



# VRCUT<sup>TM</sup> Ready TRIUMPH<sup>®</sup> 7260

- 28" programmable cutter with hydraulic clamp, power back gauge
- 7" touchpad control module
- IR safety light beams on front table
- Hydraulic clamp drive
- Foot pedal for pre-clamping
- Electric back gauge drive with control module for easy programming
- Digital measurement display with multilingual operator guidance
- Stores 99 programs with up to 99 steps in each (up to 15 repeat cuts can be integrated as a single step)
- Pre-programmed for standard paper sizes
- Memory keys for repeat cuts (manual) and quick setting of frequently needed measurements



## VRCUT<sup>TM</sup> CUT WITH CONFIDENCE



The VRCut solution consists of two independent modules that work together. The Impose module creates PDF documents formatted specifically to work with the VRCUT controller module. The controller module connects directly to the Triumph cutter moving the back gauge and visually guiding operators through the cutting sequence.

### Specifications:

Cutting width	28"
Cutting height	3"
Narrow cut	0.7" (3.5" w/ false clamp)
Length behind blade	28"
Electrical requirements	115 V, 60 Hz 20 amp dedicated line
Dimensions (D x W X H)	60.5" x 51.3" x 52.5"
With side table (D x W)	63" x 82.5"

